

Table of contents

| | | |
|-----|---------------------------------------------|---|
| 1 | About..... | 3 |
| 2 | Step..... | 4 |
| 2.1 | Make “*.cbea” file..... | 4 |
| 2.2 | Make Setup.ini..... | 4 |
| | A field name and the describing method..... | 4 |
| 2.3 | Other files..... | 5 |
| 2.4 | Install..... | 5 |
| 3 | Note..... | 6 |

1 About

This is the document of the tool which installs the application of “*.cbea” by “PC Connect”.

(“PC Connect” is CASIO Original connection software.)

Please create the file of “*.cbea” form first.

“*.cbea” file can use the thing same as installation from PC offered behind.

2 Step

2.1 Make "*.cbea" file

Please read "ArchGene.doc".

1. The following file is copied to arbitrary folders.
ArchGene.exe, MkArch.exe
2. Please copy the folder (the file to install) under that folder.
3. Please copy "native.ina" to the folder that file to install.
4. Execute ArchGene.exe

*.cbea is created.

Please refer to the following document if needed.

"Installer Archive.doc" : Each setting file information.

"Installer INF.doc" : *.Inf file Document.

```

-----ArchGene.exe      --- CASIO Original file
      MkArch.exe        --- CASIO Original file
      *.cbea (create)
      [Install]---*.exe
              *.bmp
              *.html
      native.ina--- CASIO Original file
  
```

2.2 Make Setup.ini

Setup.ini is a file for teaching the name of an application, and capacity required for installation to Setup.exe and Appmgr.exe.

If you use ArchGene.exe, Setup.ini can be created automatically.

A field name and the describing method

[APPNAME]

appname = Application name

[REGISTRY]

byte = 64000 // It is capacity required for NAND for registry preservation.
// A standard is file capacity x0.2.
// When you do not fulfill 64K, please make it 64K.

[RAM]

byte = 400000 // Capacity when being saved at RAM temporarily at the time
// of installation
// Since the inside of RAM is compressed, it becomes less
// than file capacity somewhat.

[PLACE]

drive = 3 // An installable place
// 1:MAIN_ONLY
// 2:STORAGE_ONLY
// 3:ALTERNATIVE

2.3 Other files

The following file is not necessarily required.

1. readme.txt

This is the description displayed at the time of installation.

2. License.txt

This is EULA(End-User software License Agreement) displayed at the time of installation.

2.4 Install

1. Please install "PC Connect" in your PC.
2. Please set the following file in one folder.
Setup.exe, Setup.ini, *.cbea, readme.txt, License.txt
3. The BE-300 device and PC are connected.
(When connection processing is not performed at this time, please look at the document of attachment in PC Connect.)
4. Please perform Setup.exe, if you will be in a connection state by PC connect.
5. Please push a button according to directions.

3 Note

When you have stopped during installation, please cancel connection, and reset a device.